



# SPK-TG

## SPK-TG 800

|                                     |                    |
|-------------------------------------|--------------------|
| <b>Model Name</b>                   | SPK-TG800          |
| <b>Nominal Diameter</b>             | DN 800             |
| <b>Pressure</b> [mH <sub>2</sub> O] | 3                  |
| <b>Weight</b> [kg]                  | 130                |
| <b>Closing torque</b> [Nm]          | 65                 |
| <b>Frame</b>                        | EN 1.4404 AND HDPE |
| <b>Opening torque</b> [Nm]          | 65                 |
| <b>Operating Temperature</b>        | -25° C - +40° C    |

|                             |                                 |
|-----------------------------|---------------------------------|
| <b>Revs open</b> [-]        | 160                             |
| <b>Seal against wall</b>    | EPDM Foamseal                   |
| <b>Sealing against gate</b> | EPDM                            |
| <b>Sliding Plate</b>        | EN 1.4404                       |
| <b>Spindle</b>              | EN 1.4571                       |
| <b>Spindle Nut</b>          | CuSn12                          |
| <b>Thread pitch</b> [mm]    | 5                               |
| <b>Watertightness</b>       | DIN 19569-4 table no. 1 class 5 |

## Product Variants

|                                                                                |                  |
|--------------------------------------------------------------------------------|------------------|
| <b>Name</b>                                                                    | <b>V80876800</b> |
| <b>Weight</b> [kg]                                                             | 125              |
| <b>CO<sub>2</sub> Equivalent (CO<sub>2</sub>e)</b> [kg CO <sub>2</sub> e/unit] | 686.2            |