



# SPM-P-TG

## SPM-P-TG 1000

|                              |                    |
|------------------------------|--------------------|
| Model Name                   | SPM-P-TG1000       |
| Nominal Diameter             | DN 1000            |
| Pressure [mH <sub>2</sub> O] | 6                  |
| Weight [kg]                  | 197                |
| Closing torque [Nm]          | 65                 |
| Frame                        | EN 1.4404 AND HDPE |
| Opening torque [Nm]          | 107                |
| Operating Temperature        | -25° C - +40° C    |

|                      |                                 |
|----------------------|---------------------------------|
| Revs open [-]        | 167                             |
| Seal against wall    | EPDM Foamseal                   |
| Sealing against gate | EPDM                            |
| Sliding Plate        | EN 1.4404 AND HDPE              |
| Spindle              | EN 1.4462                       |
| Spindle Nut          | CuSn12                          |
| Thread pitch [mm]    | 6                               |
| Watertightness       | DIN 19569-4 table no. 1 class 5 |

## Product Variants

|                                                                            |            |
|----------------------------------------------------------------------------|------------|
| Name                                                                       | V815761000 |
| Weight [kg]                                                                | 187.7      |
| CO <sub>2</sub> Equivalent (CO <sub>2</sub> e) [kg CO <sub>2</sub> e/unit] | 1          |