



WASTOP® INLINE CHECK VALVE

WaStop 750

Model Name	WS750	Max. ID Host Pipe [mm]	767
Nominal Diameter	DN 750	Min. ID Host Pipe [mm]	755
Max. Flow Velocity [m/s]	4	Fasteners mtrl.	EN 1.4404
Weight [kg]	90	Gasket	EPDM
Max. Flow Volume [m³/s]	1.77		

Product Variants

Name	WS750-S2-304/316	WS750-S3-304/316	WS750-S4-304/316
Membrane mtrl.	Polyurethane	Polyurethane	Polyurethane
Valve Body	EN 1.4404 / EN 1.4301	EN 1.4404 / EN 1.4301	EN 1.4404 / EN 1.4301
Max. Back Pressure [mH ₂ O]	3	5	8
Horizontal Opening [mmH ₂ O]	305	365	450
Horizontal Closing [mmH ₂ O]	190	220	270
Submerged Opening [mmH ₂ O]	185	215	245
Submerged Closing [mmH ₂ O]	60	70	90
Vertical Opening [mmH ₂ O]	425	470	515
Vertical Closing [mmH ₂ O]	180	200	220
CO ₂ Equivalent (CO ₂ e) [kg CO ₂ e/unit]	450.9 / 450.3	448.8 / 448.3	450.2 / 448.9

