



WASTOP® INLINE CHECK VALVE

WaStop 97 Short Double Collar

Model Name	WS97-SHDC
Nominal Diameter	DN 100
Max. Flow Velocity [m/s]	2
Weight [kg]	0.6
Max. Flow Volume [l/s]	16

Max. ID Host Pipe [mm]	106
Min. ID Host Pipe [mm]	96
Watertightness	EN 13564
Fasteners mtrl.	EN 1.4404
Gasket	EPDM

Product Variants

Name	WS97-C-316-SHDC	WS97-S2-316-SHDC	WS97-S3-316-SHDC	WS97-S4-316-SHDC
Membrane mtrl.	EPDM	MVQ Silicone	MVQ Silicone	MVQ Silicone
Valve Body	EN 1.4404	EN 1.4404	EN 1.4404	EN 1.4404
Max. Back Pressure [mH ₂ O]	3	2	3	3
Horizontal Opening [mmH ₂ O]	175	160	190	320
Horizontal Closing [mmH ₂ O]	70	70	70	85
Submerged Opening [mmH ₂ O]	145	125	145	165
Submerged Closing [mmH ₂ O]	20	15	20	25
Vertical Opening [mmH ₂ O]	220	170	220	240
Vertical Closing [mmH ₂ O]	80	75	80	90

